

Technical data sheet

Softwood decking

Product information



Dimensions	32 x 150mm nominal / 28 x 144mm finished
Species	European Redwood
Botanical name	Pinus Sylvestrus
Origin	Northern Europe
Sources	PEFC / FSC
Description	Dual deck board grooved 1 side / Smooth 1 side
Product features	Tanalith E pressure impregnated 15 year guarantee against rot and fungal decay Precision finish Kiln dried Hard wearing Matching accessories available

Colour	Softwood decking has a green appearance when first pressure treated. Salting (white specks on the surface of the board) will appear after a while, this is a natural part of the process and a sign of quality. Once weathered the salting will disappear and the green colour will mellow to provide a warm yellow feel.
Tanalith E treatment	Copper based pressure impregnated wood preservative
Product applications	Suitable for use class 3 or 4 applications (in or out of ground contact) Timber supports, deck skirting or deck boards
Cleaning and maintenance	Wash down regularly with a mild detergent and a stiff brush to extend the life of the decking.
Nailing and screwing	Pre-drilling is not necessary
Fixing instructions	Can be fixed using standard coated deck screws / nails or secret fix deck clips
Guarantee	15 year guarantee subject to terms and conditions supported by Arch chemicals
Product disposal	Tanalith E treated timber is a non-hazardous material therefore disposal can be through normal waste disposal facilities in line with local guidelines